

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

This finish meets ASTM D2047 method for slip resistance.

Maximum VOC Content: 274 g/L

See Product Safety Data Sheet Before Using.

For Commercial, Industrial and Institutional Use Only.

Contents: Water (7732-18-5), Acrylic Polymer (Withheld), Polyurethane Dispersion (Withheld), Propylene glycol (57-55-6), 2-butoxyethanol (111-76-2), Tributyoxyethyl phosphate (78-51-3), Ethylene glycol (107-21-1).

HMIS Ratings:

Health-1, Flammability-0, Physical Hazards-0



WARNING: Reproductive Harm -
www.P65Warnings.ca.gov.

Scan QR code for access to the Safety Data Sheet.



Net Contents: 5 Gallons (18.9 Liters)



FULL COURT FINISH PC

WATER-BASED URETHANE GYM FLOOR FINISH



Utilizes Unique Polycarbonate Technology for Increased Depth, Extended Gloss and Extreme Durability.

- Single-Component Formula-No Pot Life or Mess
- Contains Reactive Polymers That Offer Durability and Appearance Equal to or Greater Than Oil-Modified Products
- Six to Twenty-Four Hour Dry Time Between Coats Under Normal Conditions
- Large Area Coverage of Up To 900 Square Feet Per Gallon
- VOC Compliant – NMP-Free

This water-based urethane wood floor finish provides long-lasting durability and protection to all wood floors. It is a single component product that offers high durability, high depth of gloss and excellent black mark, scuff, scratch and soil resistance. It is uniquely restorable with high speed burnishing equipment.

An Exclusive Formula of

M-289

MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. Box 927 • COLUMBUS, NE 68602-0927 • 800-228-8508

DIRECTIONS

READ ALL DIRECTIONS BEFORE APPLYING.

- 1. Prepare Floor:** This finish is not designed for application to bare wood floors. Use only on previously sealed surfaces. **Scrub and Recoat:** Dust mop floor and remove all chewing gum and tape. Prepare floor by scuffing with MARC 826 X- Extreme or MARC 827 Gym Conditioning Pads. Tack or autoscrub floor using MARC 225 Big Bad Orange or MARC 267 Auto Power. **NOTE:** Test previously coated floor in an inconspicuous area before recoating to determine compatibility with existing finish. Then apply one or two coats of **MARC Full Court Finish PC** according to the directions below.
- 2. Apply Finish:** Stir gently before using. **Apply MARC Full Court Finish PC** at a rate of 700-900 square feet per gallon. The floor temperature should be a minimum of 50°F. Use a weighted T-bar with a clean, synthetic pad. When straining finish into a barrel applicator, allow finish to stand for 20 to 30 minutes before applying to floor. This will allow air bubbles to escape. Apply thin, even coats with the grain of the wood while walking at a slow, even pace. Walking too fast may produce excessive bubbling in the finish. Allow a dry time of at least 6 to 24 hours between coats. If the humidity is high (above 70%), allow at least 12 hours between coats. After the first coat has dried, apply a second coat if desired. **NOTE:** Use by expiration date stated on pail. Do not pour unused finish back into original container.
- 3. Maintain Daily:** Dust mop floor at least daily, or more as required, to keep floor free of dust and dirt. Damp mop spills, salt residue, etc. with MARC 225 or MARC 315 Fabulous and a thoroughly wrung mop.
- 4. Maintain Weekly:** If soil conditions are heavy, auto-scrub weekly with MARC 818 Blue Soft Autoscrub pads and a 2 ounce per gallon dilution of MARC 225 or MARC 267.
- 5. Restoration:** Dust mop floor. Auto-scrub with MARC 818 Blue Soft Autoscrub Pads or MARC 801 Microfiber Cleaning Pads using a 2 ounce per gallon dilution of MARC 225 Big Bad Orange or MARC 267 Auto Power Floor Cleaner. If needed, dry-burnish using a MARC 814 High Speed Hawg Hair Pad.

R0624

Made in USA